



Product Data

Optitemp SG 2

Special lubricating grease, resistant to water and high temperatures

Description

Castrol OPTITEMP™ SG 2 (previously named Rheomic™ SG 2) is a high-temperature lubricating grease for long-term and lifetime lubrication of all types of sliding points. OPTITEMP SG 2 as special lubricant is also suited for lubricating points exposed to extreme thermal and mechanical loads, e.g. for shift linkages in passenger cars.

Application

- Bearings and sliding points in the change gear system of vehicles.
- For highly loaded sliding points of all types of machines.
- Long-term and lifetime lubrication even under extreme mechanical conditions.
- For rolling and sliding bearings.
- Temperature application range: - 35°C/- 31°F to + 160°C/+ 320°F

Advantages

- Excellent corrosion protection
- High water resistance
- Wide temperature application range.
- Reduction of the coefficient of friction
- Good load carrying capacity
- Compatible with PUR materials

Typical Characteristics

Name	Method	Units	Optitemp SG 2
Colour	Visual / ASTM D1500	-	brown - natural colour
Thickener type	-	-	Polyurea
Worked Penetration (60 strokes @ 25°C / 77°F)	ASTM D217 / ISO 2137	0.1 mm	287
Base Oil Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm²/s	92
Dropping point	ASTM D566 / ISO 2176	°C/°F	268/514.4
Water Resistance	DIN 51807-1	Rating	0
Rust Test - EMCOR (distilled water)	ASTM D6138 / ISO 11007	Rating	0
VW Oil Separation test (1hr / 90°C/194°F)	P-VW-1423	% w t	3.6
Flow pressure @ -35°C/-31°F	DIN 51805	mBar	950

Subject to usual manufacturing tolerances

Additional Information

Do not mix OPTITEMP SG 2 with other lubricating greases. In case of doubt please contact the Technical Service.

This product was previously named Rheomic SG 2 . The name was changed in 2015.

Optitemp SG 2

06 Jan 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>